

# Laurel Elementary School Safe Routes to School Improvement Plan

#### A Brown Avenue

- Restripe Brown Avenue with white curb and install signage to create a 300-foot drop-off area
- Work with PTA and 5th grade teachers to establish a student valet program
- Work with Oakland PD to conduct targeted enforcement,
- reducing instances of double parking

### **B** Loma Vista Avenue at Kansas Street

- Stripe high-visibility crosswalk in northeast leg of intersection - Construct curb ramps at crosswalk
- Install a filter on the signal at MacArthur and Loma Vista so
- motorists cannot see a green signal phase until close by
- Install Assembly B, Assembly D, and SLOW SCHOOL XING
- pavement markings in advance of crosswalk
- Study warrant for four-way stop at intersection

### **G** Kansas Street at Magee Avenue

- Stripe high-visibility crosswalk in northeast leg of intersection - Construct a curb ramp on east corner

### **D** Kansas Street at 35th Avenue

- Stripe approximately 30 feet of red curb on 35th Avenue northbound, in advance of Kansas Street
- Restripe existing crosswalk in northeast leg as high-visibility - Install "Yield Here" signs and sharks teeth in advance of crosswalk - Install speed feedback signs on 35th Avenue to reduce speeds

### **G** 35th Avenue at Wisconsin Street

- Consider Rectangular Rapid-Flashing Beacon (RRFB) for crosswalk in southwest leg
- Restripe existing crosswalk as high-visibility
- Evaluate advance warning beacon for southbound, downhill
- Long term: Consider traffic calming such as lane reallocation on 35th Avenue

### G Kansas Street

- Evaluate traffic calming measures to reduce motorist speeds

## **G** Entrance at Patterson Avenue

- Construct/install concrete pavers to allow students access to bicycle parking



